

Silencers



Silencers are designed for installation on exhaust circuits to reduce the noise levels of equipment while operating, thus improving user comfort.

Technical Characteristics

- **Compatible Fluids:** Compressed air
- **Working Pressure:** Polyethylene: 0 to 10 bar
Sintered bronze: 0 to 12 bar
316L stainless steel: 0 to 12 bar
- **Working Temperature:** Polyethylene: -10°C to +80°C
Sintered bronze: -20°C to +150°C
316L stainless steel: -20°C to +180°C

Advantages


- 3 materials available :
 - Polyethylene: optimum exhaust flow rate and noise attenuation
 - Sintered bronze: robust and economic
 - 316L stainless steel: increased chemical and mechanical resistance
- Incorporated flow control regulator on 2 versions

Component Materials

Silicone-free

Body:
brass (0670-0673-0675-0671-0677-0672)
polymer (0674-0676)
stainless steel (0682-0683)

Silencer:
sintered bronze (0670-0673-0675-
0671-0677-0672)
polymer (0674-0676)
316L stainless steel (0682-0683)








Regulations

- RoHS
- REACH
- PED
- 2003/10/CE
- OSHA

0671 Push-In Silencer

Nickel-plated brass



ØD		G	L	L1	Kg
4	 0671 04 00	13	43.5	28.5	0.014
6	 0671 06 00	15	50	33.5	0.024
8	 0671 08 00	15	51	34	0.025
10	 0671 10 00	19.5	67	45.5	0.052
12	 0671 12 00	20	68	45	0.052

DYSTRYBUTOR PARKER PREMIUM

ARA[®]
PNEUMATIK

| arapneumatik.pl

PARKER STORE WROCŁAW
pneumatyka@arapneumatik.pl
TEL. 71 364 72 80

PARKER STORE KATOWICE
katowice@arapneumatik.pl
TEL . 32 779 76 40

