

# Silencers



Silencers are designed for installation on exhaust circuits to reduce the noise levels of equipment while operating, thus improving user comfort.

## Technical Characteristics

- **Compatible Fluids:** Compressed air
- **Working Pressure:** Polyethylene: 0 to 10 bar  
Sintered bronze: 0 to 12 bar  
316L stainless steel: 0 to 12 bar
- **Working Temperature:** Polyethylene: -10°C to +80°C  
Sintered bronze: -20°C to +150°C  
316L stainless steel: -20°C to +180°C

## Advantages


- 3 materials available :
  - Polyethylene: optimum exhaust flow rate and noise attenuation
  - Sintered bronze: robust and economic
  - 316L stainless steel: increased chemical and mechanical resistance
- Incorporated flow control regulator on 2 versions

## Component Materials

### Silicone-free

**Body:**  
brass (0670-0673-0675-0671-0677-0672)  
polymer (0674-0676)  
stainless steel (0682-0683)

**Silencer:**  
sintered bronze (0670-0673-0675-0671-0677-0672)  
polymer (0674-0676)  
316L stainless steel (0682-0683)




## Regulations

- RoHS
- REACH
- PED
- 2003/10/CE
- OSHA

## 0673 Compact Silencer, Male BSPP and Metric Thread

Brass



C		E	F	H	Kg
M5x0.8	 <b>0673 00 19</b>	4	8	8.5	0.001
G1/8	<b>0673 00 10</b>	6	13	12	0.008
G1/4	<b>0673 00 13</b>	8	16	16	0.012
G3/8	<b>0673 00 17</b>	8	19	17	0.022
G1/2	<b>0673 00 21</b>	9	24	18	0.041

DYSTRYBUTOR PARKER PREMIUM

**ARA**<sup>®</sup>  
PNEUMATIK

| arapneumatik.pl

PARKER STORE WROCŁAW  
pneumatyka@arapneumatik.pl  
TEL. 71 364 72 80

PARKER STORE KATOWICE  
katowice@arapneumatik.pl  
TEL. 32 779 76 40

