

# Silencers



Silencers are designed for installation on exhaust circuits to reduce the noise levels of equipment while operating, thus improving user comfort.

## Technical Characteristics

- **Compatible Fluids:** Compressed air
- **Working Pressure:** Polyethylene: 0 to 10 bar  
Sintered bronze: 0 to 12 bar  
316L stainless steel: 0 to 12 bar
- **Working Temperature:** Polyethylene: -10°C to +80°C  
Sintered bronze: -20°C to +150°C  
316L stainless steel: -20°C to +180°C

## Advantages


- 3 materials available :
  - Polyethylene: optimum exhaust flow rate and noise attenuation
  - Sintered bronze: robust and economic
  - 316L stainless steel: increased chemical and mechanical resistance
- Incorporated flow control regulator on 2 versions

## Component Materials

### Silicone-free

**Body:**  
brass (0670-0673-0675-0671-0677-0672)  
polymer (0674-0676)  
stainless steel (0682-0683)

**Silencer:**  
sintered bronze (0670-0673-0675-0671-0677-0672)  
polymer (0674-0676)  
316L stainless steel (0682-0683)




## Regulations

- RoHS
- REACH
- PED
- 2003/10/CE
- OSHA

## 0677 Miniature Silencer, Male BSPP Thread

Brass



C		G	H	Kg
G1/8	<b>0677 00 10</b>	5.5	4	0.002
G1/4	<b>0677 00 13</b>	6	4.5	0.003
G3/8	<b>0677 00 17</b>	9.5	5	0.006
G1/2	<b>0677 00 21</b>	12.5	5.5	0.010
G3/4	<b>0677 00 27</b>	19	6	0.019
G1	<b>0677 00 34</b>	24	7	0.025

DYSTRYBUTOR PARKER PREMIUM

**ARA**<sup>®</sup>  
PNEUMATIK

| arapneumatik.pl

PARKER STORE WROCLAW  
pneumatyka@arapneumatik.pl  
TEL . 71 364 72 80

PARKER STORE KATOWICE  
katowice@arapneumatik.pl  
TEL . 32 779 76 40

