

Silencers



Silencers are designed for installation on exhaust circuits to reduce the noise levels of equipment while operating, thus improving user comfort.

Technical Characteristics

- **Compatible Fluids:** Compressed air
- **Working Pressure:** Polyethylene: 0 to 10 bar
Sintered bronze: 0 to 12 bar
316L stainless steel: 0 to 12 bar
- **Working Temperature:** Polyethylene: -10°C to +80°C
Sintered bronze: -20°C to +150°C
316L stainless steel: -20°C to +180°C

Advantages


- 3 materials available :
 - Polyethylene: optimum exhaust flow rate and noise attenuation
 - Sintered bronze: robust and economic
 - 316L stainless steel: increased chemical and mechanical resistance
- Incorporated flow control regulator on 2 versions

Component Materials

Silicone-free

Body:
brass (0670-0673-0675-0671-0677-0672)
polymer (0674-0676)
stainless steel (0682-0683)

Silencer:
sintered bronze (0670-0673-0675-0671-0677-0672)
polymer (0674-0676)
316L stainless steel (0682-0683)




Regulations

- RoHS
- REACH
- PED
- 2003/10/CE
- OSHA

0683 Compact Silencer, Male NPT Thread

Stainless steel 316L



C		E	F	G	H	Kg
NPT1/8	0683 00 11	7	7	14	14	0.008
NPT1/4	0683 00 14	11	7	17	18	0.014
NPT3/8	0683 00 18	11	8	22	19	0.021
NPT1/2	0683 00 22	15	10	27	25	0.042

DYSTRYBUTOR PARKER PREMIUM

ARA[®]

PNEUMATIK

| arapneumatik.pl

PARKER STORE WROCŁAW
pneumatyka@arapneumatik.pl
TEL. 71 364 72 80

PARKER STORE KATOWICE
katowice@arapneumatik.pl
TEL. 32 779 76 40

