






CA **Female Metric 24°
Light Series with O-Ring
Swivel – Straight**

ISO 12151-2-SWS-L – DKOL



XXXXX-XX-XX Part Number 	 Hose I.D.				 Thread metric	Tube O.D. mm	A mm	B mm	 W mm
	DN	Inch	Size	mm					
3CA82-6-4	6	1/4	-4	6.3	M12x1.5	6	40	21	14
3CA82-6-4B	6	1/4	-4	6.3	M12x1.5	6	40	21	14
3CA82-8-4	6	1/4	-4	6.3	M14x1.5	8	36	17	17
3CA82-8-4B	6	1/4	-4	6.3	M14x1.5	8	36	17	17
3CA82-10-4	6	1/4	-4	6.3	M16x1.5	10	36	17	19
3CA82-10-6	10	3/8	-6	9.5	M16x1.5	10	40	17	19
3CA82-10-6B	10	3/8	-6	9.5	M16x1.5	10	39	17	19
3CA82-12-6	10	3/8	-6	9.5	M18x1.5	12	40	17	22
3CA82-12-6B	10	3/8	-6	9.5	M18x1.5	12	39	17	22
3CA82-15-8	12	1/2	-8	12.7	M22x1.5	15	44	18	27
3CA82-15-8B	12	1/2	-8	12.7	M22x1.5	15	44	17	27
3CA82-15-10B	16	5/8	-10	15.9	M22x1.5	15	60	23	27
3CA82-18-10	16	5/8	-10	15.9	M26x1.5	18	56	19	32
3CA82-22-12	20	3/4	-12	19.1	M30x2	22	58	21	36
3CA82-22-12B	20	3/4	-12	19.1	M30x2	22	58	21	36

Fittings with standard O-ring seals can be used for temperatures from -30 °C up to +105 °C.

Parker Dystrybutor:


ARA[®]
PNEUMATIK
53-012 Wrocław ul. Wyścigowa 38
www.arapneumatik.pl



Also available in stainless steel. Details can be found in CAT 4400.1/UK

Approved **fitting series** for hose types:

B: Brass; K: Without plastic ring; SM: Metric Hexagon

82  801 804 821FR 830M 831 836 837BM 837PU 838M