






**D0**      **Male Metric 24°  
Light Series – Rigid  
Straight**

ISO 12151-2-S-L – CEL



XXXXX-XX-XX Part Number 	 Hose I.D.				 Thread metric	Tube O.D.	A	B	 H
	DN	Inch	Size	mm		mm	mm	mm	mm
3D082-6-4	6	1/4	-4	6.3	M12x1.5	6	35	16	12
3D082-8-4	6	1/4	-4	6.3	M14x1.5	8	36	17	14
3D082-8-4B	6	1/4	-4	6.3	M14x1.5	8	36	17	14
3D082-10-6	10	3/8	-6	9.5	M16x1.5	10	41	18	17
3D082-10-6B	10	3/8	-6	9.5	M16x1.5	10	41	18	17
3D082-12-6	10	3/8	-6	9.5	M18x1.5	12	41	18	19
3D082-12-6B	10	3/8	-6	9.5	M18x1.5	12	41	18	19
3D082-15-8	12	1/2	-8	12.7	M22x1.5	15	49	23	22
3D082-15-8B	12	1/2	-8	12.7	M22x1.5	15	49	22	22
3D082-18-8	12	1/2	-8	12.7	M26x1.5	18	48	21	27
3D082-18-10	16	5/8	-10	15.9	M26x1.5	18	58	21	27
3D082-18-10B	16	5/8	-10	15.9	M26x1.5	18	58	21	27
3D082-22-12	20	3/4	-12	19.1	M30x2	22	63	27	30
3D082-22-12B	20	3/4	-12	19.1	M30x2	22	63	27	30

Also available in stainless steel. Details can be found in CAT 4400.1/UK


Parker Dystrybutor:

**ARA**<sup>®</sup>  
PNEUMATIK  
53-012 Wrocław ul. Wyścigowa 38  
[www.arapneumatik.pl](http://www.arapneumatik.pl)



Approved **fitting series** for hose types:

B: Brass; K: Without plastic ring; SM: Metric Hexagon

**82**  801 804 821FR 830M 831 836 837BM 837PU 838M