


0690 02**Safety nozzle**


C	DN		G	L	L1	
M12x1,25	3	0690 02 00	15	31,2	9,2	0,025



315 NI/min



OSHA 1910.242 (b)
 OSHA 1910.95 (b)
 Directive 2003/10/EC :
 Hearing protectors should always
 be worn when exposure to noise
 lasts longer than 8 hours.

0690 03**Straight tube nozzle (long)**


C	DN		G	L	L1	
M12x1,25	2,5	0690 03 00	15	332	307	0,065



365 NI/min



OSHA 1910.95 (b)
 Directive 2003/10/EC : Hearing
 protectors should always be worn
 when exposure to noise lasts longer
 than 8 hours.

0690 04**Straight tube nozzle (short)**


C	DN		G	L	L1	
M12x1,25	2,5	0690 04 00	15	102	77	0,035



385 NI/min



OSHA 1910.242 (b)
 OSHA 1910.95 (b)
 Directive 2003/10/EC : Hearing
 protectors should always be worn
 when exposure to noise lasts
 longer than 8 hours.

0690 07**Safety nozzle**


ØD	C		G	L	L1	
4	M12x1,25	0690 07 00	15	35	12,7	0,025



330 NI/min
 (without tube)
 266 NI/min
 (with tube 2,5x4)
 158 NI/min
 (with tube 2x4)



OSHA 1910.95 (b)
 Directive 2003/10/EC :
 Hearing protectors should
 always be worn when exposure
 to noise lasts longer than 8 hours.

0690 08**Coanda effect nozzle**


C		L	L1	
M12x1,25	0690 08 00	47,5	26	0,033



240 NI/min



OSHA 1910.242 (b)
 OSHA 1910.95 (b)
 Directive 2003/10/EC :
 No hearing protectors
 should be worn

0690 09**Air screen nozzle**


C	DN		G	L	L1	
M12x1,25	2	0690 09 00	30	40,5	18,5	0,021



650 NI/min



OSHA 1910.242 (b)
 OSHA 1910.95 (b)
 Directive 2003/10/EC :
 Hearing protectors should
 always be worn

0690 10**Booster nozzle**

C	DN		G	L	L1	
M12x1,25	2,5	0690 10 00	15	64	42	0,038



335 NI/min



OSHA 1910.242 (b)
 Directive 2003/10/EC :
 Hearing protectors should
 always be worn

ARA[®]
PNEUMATIK

53-012 Wrocław tel. 71 364 72 82
 ul. Wyciągowa 38 fax 71 364 72 83

www.arapneumatik.pl

