



European Profile




9401E Coupler, Male BSPP Thread

	Technical polymer, nickel-plated brass, NBR 		C	E	F	G	L	kg	
		G1/4	9401E07 13	6.5	22	36.5	80	0.124	
		7.2	G3/8	9401E07 17	7.5	22	36.5	81	0.122
		G1/2	9401E07 21	9	25	36.5	83.5	0.136	


C 9000 Series: single shut-off = 2000 NI/min

9414E Coupler, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 		C	E	F	G	L	kg	
		G1/4	9414E07 13	12	22	36.5	73	0.118	
		7.2	G3/8	9414E07 17	12	22	36.5	73	0.109
			G1/2	9414E07 21	15	27	36.5	78	0.130


C 9000 Series: single shut-off = 2000 NI/min

9410E Coupler, LF 3000® Push-In Connection, with Spiral Protection Spring

	Technical polymer, nickel-plated brass, NBR 		ØD		G	L	L1	kg
		7.2	10	9410E07 10	36.5	151	63	0.175
			12	9410E07 12	36.5	151	63	0.180


C 9000 Series: single shut-off = 2000 NI/min

9421E Coupler with Hosetail

	Technical polymer, nickel-plated brass, NBR 		ØD	F	G	L	L1	kg	
			8	9421E07 08	22	36.5	93	26	0.113
		7.2	10	9421E07 10	22	36.5	93	26	0.114
			13	9421E07 13	22	36.5	97	30	0.119

C 9000 Series: single shut-off = 2000 NI/min

9416E Coupler, Bulkhead Mountable, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 		C	E	F	G	K _{max}	L1	L2	ØT _{min}	kg	
		7.2	G3/8	9416E07 17	12	24	36.5	7	14.5	74	22.5	0.153
		C 9000 Series: single shut-off = 2000 NI/min										

ARA®


PNEUMATIK

53-012 Wrocław tel. 71 364 72 82
ul. Wyścigowa 38 fax 71 364 72 83

www.arapneumatik.pl




European Profile



9440E Y Coupler, Female BSPP Thread



Technical polymer, nickel-plated brass, NBR




	C		E	F	F1	G	H	H1	kg
7.2	G1/2	9440E07 21	14	25	25	36.5	78	19	0.335

C 9000 Series: single shut-off = 2000 NI/min

9087E Probe, Straight-Through, Male BSPP Thread



Nickel-plated steel, technical polymer




DN	C	E	F	L	L1	kg
7.2	G1/4 9087E07 13	9	14	34	20	0.018
	G3/8 9087E07 17	9	17	34	20	0.025
	G1/2 9087E07 21	12	22	38	20	0.048

Probe without shut-off

9086E Probe, Straight-Through, Female BSPP Thread



Nickel-plated steel




	C	E	F	L	L1	kg
7.4	G1/8 9086 25 10	7	14	32	20	0.015
	G1/4 9086 25 13	9	17	38.5	20	0.027
	G3/8 9086 25 17	9	19	33	20	0.027
	G1/2 9086 25 21	12	24	36	20	0.050

Probe without shut-off

9080E Probe, Straight-Through, LF 3000® Push-In Connection, with Spiral Protection Spring



Nickel-plated steel, NBR




	ØD		G	L	L1	kg
7.2	10	9080E07 10	24	114	20	0.102
	12	9080E07 12	29.5	125	20	0.088

Probe without shut-off

9094E Probe, Straight-Through, with Hosetail



Nickel-plated steel



	ØD		F	L	L1	L2	kg
7.2	8	9094E07 08	17	48	20	25	0.014
	10	9094E07 10	17	48	20	25	0.016
	13	9094E07 13	17	48	20	25	0.019

Probe without shut-off

