


ISO B Profile



9401U Coupler, Male BSPP Thread

Technical polymer, nickel-plated
brass, NBR

C

E

F

G

L

kg

5.5

G1/4

9401U06 13

7.5

17

31.5

74

0.075

G3/8

9401U06 17

8.5

21

31.5

76.5

0.095

G1/2

9401U06 21

10.5

25

31.5

80

0.115

8

G1/4

9401U08 13

6.5

22

36.5

81.5

0.120

G3/8

9401U08 17

7.5

22

36.5

82.5

0.133

G1/2

9401U08 21

9

25

36.5


85.5

0.140

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9405U Coupler, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR 		C	F	G	L	kg	
		5.5	R1/4	9405U06 13	17	31.5	75	0.075
			R3/8	9405U06 17	19	31.5	76.5	0.095
			R1/2	9405U06 21	22	31.5	81.5	0.110
		8	R1/4	9405U08 13	22	36.5	84	0.120
			R3/8	9405U08 17	22	36.5	84	0.120
R1/2	9405U08 21		22	36.5	88	0.140		

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9414U Coupler, Female BSPP Thread


Technical polymer, nickel-plated
brass, NBR

	C	E	F	G	L	kg
5.5	G1/4 9414U06 13	12	17	31.5	68.5	0.070
	G3/8 9414U06 17	12	22	31.5	72	0.085
	G1/2 9414U06 21	15	27	31.5	78	0.115
8	G1/4 9414U08 13	12	22	36.5	75	0.127
	G3/8 9414U08 17	12	22	36.5	75	0.144
	G1/2 9414U08 21	15	27	36.5	80	0.138

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min


9410U Coupler, LF 3000® Push-In Connection, Body Spiral Protection Spring

	Technical polymer, nickel-plated brass, NBR 		ØD		G	L	L1	kg
		5.5	8	9410U06 08	31.5	145	56	0.096
			10	9410U06 10	31.5	145	56	0.080
		8	10	9410U08 10	36.5	155	63	0.175
			12	9410U08 12	36.5	165	63	0.162

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 NI/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 NI/min

9421U Coupler with Hosetail


	Technical polymer, nickel-plated brass, NBR 		ØD		F	G	L	L1	kg
		5.5	6	9421U06 06	17	31.5	88.5	26	0.070
			8	9421U06 08	17	31.5	88.5	26	0.070
			10	9421U06 10	17	31.5	88.5	26	0.070
		8	6	9421U08 06	22	36.5	95	26	0.110
			8	9421U08 08	22	36.5	95	26	0.100
			10	9421U08 10	22	36.5	95	26	0.124
			13	9421U08 13	22	36.5	99	30	0.125

C 9000 Series ISO B (DN 5.5): single shut-off flow = 1250 NI/min


C 9000 Series ISO B (DN 8): single shut-off flow = 2400 NI/min



ISO B Profile



9416U Coupler, Bulkhead Mountable, Female BSPP Thread

	Technical polymer, nickel-plated brass, NBR 		C	E	F	G	K _{max}	L1	L2	ØT _{min}	kg	
		5.5	G1/4	9416U06 13	12	22	31.5	6	12.5	68.5	18.5	0.105
		8	G3/8	9416U08 17	12	24	36.5	7	14.5	76	22.5	0.150
C 9000 Series ISO B (DN 5.5): single shut-off = 1250 Nl/min C 9000 Series ISO B (DN 8): single shut-off = 2400 Nl/min												

9440U Y Coupler, Female BSPP Thread

C

E

F

F1

G

H

H1

kg

5.5

G3/8

[9440U06 17](#)

11.5

19

20

31.5

70

16

0.207

8

G1/2

[9440U08 21](#)

14

22

25

36.5

80

19

0.352

C 9000 Series ISO B (DN 5.5): single shut-off = 1250 Nl/min

C 9000 Series ISO B (DN 8): single shut-off = 2400 Nl/min

9087U Probe, Straight-Through, Male BSPP Thread

Nickel-plated steel, technical
polymer

C

E

F

L

L1

kg

5.5

8

G1/4

G3/8

G1/2

G1/4

G3/8

G1/2

[9087U06 13](#)

[9087U06 17](#)

[9087U06 21](#)

[9087U08 13](#)

[9087U08 17](#)

[9087U08 21](#)

9

9

12

9

9

12

17

19

22

17

19

22

38

38

42

38

39

42

24

24

24

24

24

24

0.025

0.032

0.048


0.030

0.036


0.058

Probe without shut-off


9086U Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel 		C	E	F	L	L1	kg	
		5.5	G1/4	9086 23 13	9	17	36	24	0.025
			G3/8	9086 23 17	9	19	36	24	0.025
			G1/2	9086 23 21	12	24	39	24	0.039
		Probe without shut-off							

9086U Probe, Straight-Through, Female BSPP Thread

	Nickel-plated steel 		C	E	F	L	L1	kg
		G1/4	9086 30 13	10	17	40	28	0.032
		G3/8	9086 30 17	10	19	42	28	0.035
		G1/2	9086 30 21	12	24	43	28	0.046
Probe without shut-off 30 Series probe (DN 8.5) compatible with ISO B series C 9000 couplers (DN 8)								

ISO B Profile



9080U Probe, Straight-Through, LF 3000® Push-In Connection, with Spiral Protection Spring

	Nickel-plated steel, NBR		ØD		G	L	L1	kg
		5.5	8	9080U06 08	24	112	24	0.052
			10	9080U06 10	24	112	24	0.044
		8	10	9080U08 10	24	114	26	0.095
			12	9080U08 12	29.5	125	26	0.096

Probe without shut-off

9094U Probe, Straight-Through, with Hosetail

	Nickel-plated steel		ØD		F	L	L1	L2	kg
		5.5	6	9094U06 06	14	51	24	25	0.016
			8	9094U06 08	14	51	27	25	0.017
			10	9094U06 10	14	51	24	25	0.018
		8	8	9094U08 08	17	51	24	25	0.027
			10	9094U08 10	17	51	27	25	0.028
			13	9094U08 13	17	51	24	25	0.031

Probe without shut-off

