



European Profile 25, 26 and 27 Series



9101 Coupler, Male BSPP Thread

	Nickel-plated brass, NBR			C	E	F	G	L	kg	
			7.2	G1/8	9101 26 10	9	22	27	43	0.073
				G1/4	9101 26 13	9	22	27	43	0.073
				G3/8	9101 26 17	9	22	27	13	0.075
				G1/2	9101 26 21	12	22	27	46	0.087

25 Series (DN 7.2): single shut-off = 1000 NL/min

9201 Coupler, Male BSPP Thread

Nickel-plated brass, NBR

C

E

F

G

L

kg

7.4

G1/4

9201 25 13

9

19

23

57

0.095

G3/8

9201 25 17

9

19

23

57

0.097

G1/2

9201 25 21

12

22

23

60

0.135

G3/8

9201 27 17

9

24

27

65

0.160

10

G1/2

9201 27 21

12

24

27

70

0.166

G3/4

9201 27 27

16

27

27


74

0.239

25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min

27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min


9214 Coupler, Female BSPP Thread

	Nickel-plated brass, NBR 		C	E	F	G	L	kg	
		7.4	G1/4	9214 25 13	9	19	23	55	0.098
			G3/8	9214 25 17	9	19	23	55	0.092
			G1/2	9214 25 21	12	24	23	57	0.124
		10	G3/8	9214 27 17	12	24	27	68	0.177
			G1/2	9214 27 21	12	24	27	68	0.166
G3/4	9214 27 27		16	32	27	74	0.255		

25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min

27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min

9114 Coupler, Female BSPP Thread


	Nickel-plated brass, NBR 		C	E	F	G	L	kg
		G1/4	9114 26 13	9	22	27	43	0.089
		G3/8	9114 26 17	9	22	27	43	0.084
		G1/2	9114 26 21	12	24	27	46	0.090

26 Series (DN 7.2): single shut-off = 1000 NL/min

9223 Coupler with Barb Connection



Nickel-plated brass, NBR



DN	ØD	F	G	L	L1	kg
7.4	6 9223 25 06	19	23	73	25	0.095
	8 9223 25 08	19	23	73	25	0.097
	10 9223 25 10	19	23	73	25	0.097
	13 9223 25 13	19	23	73	25	0.099
10	8 9223 27 08	24	27	80	21	0.146
	10 9223 27 10	24	27	80	21	0.162
	13 9223 27 13	24	27	80	21	0.164
	19 9223 27 19	24	27	80	21	0.168


25 Series (DN 7.4): single shut-off = 1800 NL/min / 25 Series (DN 7.4): double shut-off = 710 NL/min

27 Series (DN 10): single shut-off = 2400 NL/min / 27 Series (DN 7.4): double shut-off = 900 NL/min



European Profile

25, 26 and 27 Series



9087 Probe, Straight-Through, Male BSPP Thread

Nickel-plated steel, technical polymer

C

E

F

L

L1

kg

7.4

G1/8 [9087 25 10](#)

7 13 31 20 0.018

G1/4 [9087 25 13](#)

9 14 34 20 0.018

G3/8 [9087 25 17](#)

9 17 34 20 0.025

G1/2 [9087 25 21](#)

12 22 38 20 0.047

10

G3/8 [9087 27 17](#)

9 19 37 22 0.031

G1/2 [9087 27 21](#)

12 22 40 22 0.046

G3/4 [9087 27 27](#)

16 32 45 22 0.085

Probe without shut-off

25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)

9086 Probe, Straight-Through, Female BSPP Thread



Nickel-plated steel



		C	E	F	L	L1	kg
7.4	G1/8	9086 25 10	7	14	32	20	0.015
	G1/4	9086 25 13	9	17	38.5	20	0.027
	G3/8	9086 25 17	9	19	33	20	0.027
	G1/2	9086 25 21	12	24	36	20	0.050
10	G3/8	9086 27 17	9	19	34	22	0.026
	G1/2	9086 27 21	12	24	38	22	0.041
	G3/4	9086 27 27	16	32	42	22	0.090


Probe without shut-off

25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)

9085 Probe, Straight-Through, with Barb Connection



Nickel-plated steel



	DN	ØD		L	L1	L2	kg
7.4	6	9085 25 06		48	20	25	0.013
	8	9085 25 08		48	20	25	0.015
	9	9085 25 09		48	20	25	0.015
	10	9085 25 10		48	20	25	0.016
	13	9085 25 13		48	20	25	0.020
10	8	9085 27 08		48	22	25	0.021
	10	9085 27 10		48	22	25	0.023
	13	9085 27 13		48	22	25	0.026
	19	9085 27 19		48	22	25	0.038


Probe without shut-off

25 Series probe (DN 7.4) compatible with 26 Series coupler (DN 7.2)

9287 Probe, Valved, Male BSPP Thread



Nickel-plated brass, NBR




	DN	C	E	F	L	L1	kg
7.4		G1/8 9287 25 10	7	22	41	20	0.046
		G1/4 9287 25 13	9	22	43	20	0.046
		G3/8 9287 25 17	9	22	43	20	0.049
		G1/2 9287 25 21	12	22	46	20	0.060
10		G3/8 9287 27 17	9	24	58	22	0.086
		G1/2 9287 27 21	12	24	58	22	0.090
		G3/4 9287 27 27	16	27	62	22	0.132

Probe with shut-off

25 Series probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

European Profile

25, 26 and 27 Series



9286 Probe, Valved, Female BSPP Thread

DN	C	E	F	L	L1	kg
7.4	G1/8 9286 25 10	10	22	43	20	0.068
	G1/4 9286 25 13	10	22	43	20	0.062
	G3/8 9286 25 17	10	22	43	20	0.058
10	G1/2 9286 25 21	12	24	46	20	0.064
	G3/8 9286 27 17	9	24	55	22	0.096
	G1/2 9286 27 21	12	24	55	22	0.086
	G3/4 9286 27 27	16	32	58	22	0.149

Nickel-plated steel, NBR

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

9285 Probe, Valved, with Barb Connection

DN	ØD	F	L	L1	L2	kg
7.4	6 9285 25 06	21	60	20	25	0.047
	8 9285 25 08	21	60	20	25	0.048
	10 9285 25 10	21	60	20	25	0.049
10	13 9285 25 13	21	60	20	25	0.053
	8 9285 27 08	24	75	22	25	0.097
	10 9285 27 10	24	75	22	25	0.099
	13 9285 27 13	24	75	22	25	0.103
	19 9285 27 19	24	75	22	25	0.105

Nickel-plated steel, NBR

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

9293 Probe, Valved, Anti-Whiplash, Female BSPP Thread

DN	C	E	F	L	L1	kg
7.4	G3/8 9293 25 17	10	22	43	20	0.052

Nickel-plated steel, NBR

Probe with shut-off
25 Series Probe (DN 7.4) not compatible with 26 Series coupler (DN 7.2)

ARA[®]
PNEUMATIK

53-012 Wrocław tel. 71 364 72 82
ul. Wyciągowa 38 fax 71 364 72 83
www.arapneumatik.pl



legris 8-29

Metal

Quick-Acting Couplers