



Seria: VL
DN15 ÷ DN200

Zawory kulowe
ze stali nierdzewnej
ręczne

Dane ogólne:

Temperatura pracy
od -20°C do +200°C

- korpus: stal nierdzewna 1.4408,
- kula: stal nierdzewna 1.4401,
- uszczelnienie: PTFE, wzmocnione.

Zawór kulowy, 1-częściowy

VL 201



C	DN	PN	Kody zam.
G 1/4	8	63	VL 201-1/4
G 3/8	10	63	VL 201-3/8
G 1/2	15	63	VL 201-1/2
G 3/4	20	63	VL 201-3/4
G 1	25	63	VL 201-1
G 1 1/4	32	63	VL 201-1 1/4
G 1 1/2	40	63	VL 201-1 1/2
G 2	50	63	VL 201-2

Zawór kulowy, 2-częściowy

VL 451/VL 401



C	DN	PN	Kody zam.
G 1/4	8	63	VL 451-1/4
G 3/8	10	63	VL 451-3/8
G 1/2	15	63	VL 451-1/2
G 3/4	20	63	VL 451-3/4
G 1	25	63	VL 451-1
G 1 1/4	32	63	VL 451-1 1/4
G 1 1/2	40	63	VL 451-1 1/2
G 2	50	63	VL 451-2
G 2 1/2	65	63	VL 401-2 1/2
G 3	80	63	VL 401-3

Zawór kulowy, 2-częściowy

VL 402



C	DN	PN	Kody zam.
G 1/4	8	100	VL 402-1/4
G 3/8	10	100	VL 402-3/8
G 1/2	15	100	VL 402-1/2
G 3/4	20	100	VL 402-3/4
G 1	25	100	VL 402-1
G 1 1/4	32	100	VL 402-1 1/4
G 1 1/2	40	100	VL 402-1 1/2
G 2	50	100	VL 402-2

Zawór 3-częściowy z gwintami wewnętrznymi

VL 551T



C	DN	PN	Kody zam.
G 1/4	8	63	VL 551T-1/4
G 3/8	10	63	VL 551T-3/8
G 1/2	15	63	VL 551T-1/2
G 3/4	20	63	VL 551T-3/4
G 1	25	63	VL 551T-1
G 1 1/4	32	63	VL 551T-1 1/4
G 1 1/2	40	63	VL 551T-1 1/2
G 2	50	63	VL 551T-2
G 2 1/2	65	63	VL 551T-2 1/2
G 3	80	63	VL 551T-3
G 4	100	63	VL 551T-4

Zawór 3-częściowy z końcówkami do wspawania

VL 551B



DN	PN	Kody zam.
8	63	VL 551B-8
10	63	VL 551B-10
15	63	VL 551B-15
20	63	VL 551B-20
25	63	VL 551B-25
32	63	VL 551B-32
40	63	VL 551B-40
50	63	VL 551B-50
65	63	VL 551B-65
80	63	VL 551B-80
100	63	VL 551B-100

Zawór 3-częściowy z końcówkami kołnierzowymi

VL 540F



DN	PN	Kody zam.
15	40	VL 540F-15
20	40	VL 540F-20
25	40	VL 540F-25
32	40	VL 540F-32
40	40	VL 540F-40
50	40	VL 540F-50
65	40	VL 540F-65
80	40	VL 540F-80
100	40	VL 540F-100

Zawór kołnierzowy kompaktowy

VL 160F



DN	PN	Kody zam.
15	16	VL 160F-15
20	16	VL 160F-20
25	16	VL 160F-25
32	16	VL 160F-32
40	16	VL 160F-40
50	16	VL 160F-50
65	16	VL 160F-65
80	16	VL 160F-80
100	16	VL 160F-100

Zawór kołnierzowy długość zabudowy wg DIN 3202 - F4

VL 851



DN	PN	Kody zam.
15	40	VL 851-15
20	40	VL 851-20
25	40	VL 851-25
32	40	VL 851-32
40	40	VL 851-40
50	40	VL 851-50
65	16	VL 851-65
80	16	VL 851-80
100	16	VL 851-100

