



# Parker Legris: Nickel-Plated Brass Accessories

aerospace  
climate control  
electromechanical  
filtration  
fluid & gas handling  
hydraulics  
pneumatics  
process control  
sealing & shielding



ENGINEERING YOUR SUCCESS.

**ARA**<sup>®</sup>  
PNEUMATIK

53-012 Wrocław tel. 71 364 72 82  
ul. Wysycigowa 38 fax 71 364 72 83

[www.arapneumatik.pl](http://www.arapneumatik.pl)





This document presents our enhanced range of nickel-plated brass accessories, including new configurations.

Find the complete Parker Legris offer in our 2013 general Catalogue.

**Together, we can** connect you to the best in technology.  
Better than ever before.

# A Complete Range of Adaptors

## Nickel-Plated Brass Adaptors

**0912**  
BSPP/Metric  
Page 5



**0921**  
Metric  
Page 5



**0913**  
BSPT/BSPP  
Page 5



**0922**  
Metric  
Page 5



**0914**  
BSPT  
Page 5



**0910**  
BSPP  
Page 6



**0911**  
BSPT/BSPP  
Page 6



**0915**  
BSPP/Metric  
Page 6



**0923**  
Metric  
Page 6



**0916**  
BSPT/BSPP  
Page 6



**0924**  
Metric  
Page 7



**0917**  
BSPT/BSPP  
Page 7



**0927**  
BSPT  
Page 7



**0928**  
BSPT/BSPP  
Page 7



**0932**  
BSPT/BSPP  
Page 7



**0908**  
BSPP  
Page 8



**0909**  
BSPT/BSPP  
Page 8



**0903**  
BSPP  
Page 8



**0904**  
BSPT/BSPP  
Page 8



**0905**  
BSPP/Metric  
Page 8



**0933**  
BSPT/BSPP  
Page 9



**0906**  
BSPP/Metric  
Page 9



**0907**  
BSPP  
Page 9



**0920**  
BSPP/Metric  
Page 9



**0900**  
BSPT  
Page 10



**0901**  
BSPP/Metric  
Page 10



**0192**  
BSPT/BSPP  
Page 10



**0902**  
BSPP/Metric  
Page 10



**0191**  
BSPP  
Page 11



**0931**  
BSPP  
Page 11



**0934**  
BSPT  
Page 11



**0935**  
BSPP  
Page 12



New

New

New

New

## Nickel-Plated Brass Hollow Hex Plugs

**0936**  
BSPT  
Page 13



New

**0919**  
BSPP/Metric  
Page 13



# Adaptors and Plugs

Parker Legris offers a **wide range of adaptors** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

## Product Advantages

- Large Range & Flexibility**
  - A complete offer, including adaptors and plugs
  - Surface treatment for increased corrosion resistance: nickel-plated brass
  - BSPP, BSPT and metric threads
- Performance**
  - Robust design
  - Forged shapes for mechanical strength



## Technical Characteristics

<b>Products</b>	Adaptors and Plugs
<b>Working Pressure</b>	60 bar
<b>Working Temperature</b>	-10°C to +80°C

### Component Material



New configurations are now available.



**0933**



**0934**






**0935**






**0936**

# Nickel-Plated Brass Adaptors




## 0912 Equal Stud Elbow, Female BSPP and Metric Thread

	Nickel-plated brass 	<b>C</b>		<b>E</b>	<b>G</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		M5x0.8	<a href="#">0912 00 19</a>	4	8	9	11	0.006
		G1/8	<a href="#">0912 00 10</a>	8	13	10	18.5	0.015
		G1/4	<a href="#">0912 00 13</a>	11	17	12	22.5	0.028
		G3/8	<a href="#">0912 00 17</a>	11.5	21	15	25.5	0.043
		G1/2	<a href="#">0912 00 21</a>	14	26	19	30	0.073
		G3/4	<a href="#">0912 00 27</a>	16.5	32	22	35.5	0.143
		G1	<a href="#">0912 00 34</a>	18	38.5	28	40.5	0.166




## 0921 Equal Stud Elbow, Male/Female, Metric Thread

	Nickel-plated brass 	<b>C</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		M5x0.8	<a href="#">0921 00 19</a>	4	8	11	9	11	0.006




## 0913 Equal Stud Elbow, Male BSPT/ Female BSPP Thread

	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0913 00 10</a>	8	13	17	10	18.5	0.012
		R1/4	G1/4	<a href="#">0913 00 13</a>	11	17	22.5	12	22.5	0.026
		R3/8	G3/8	<a href="#">0913 00 17</a>	11.5	21	25.5	15	25.5	0.038
		R1/2	G1/2	<a href="#">0913 00 21</a>	14	26	30	19	30	0.064
		R3/4	G3/4	<a href="#">0913 00 27</a>	16.5	32	34.5	22	35.5	0.098
		R1	G1	<a href="#">0913 00 34</a>	18	38.5	40.5	28	40.5	0.146

## 0922 Equal Stud Elbow, Male Metric Thread




	Nickel-plated brass 	<b>C</b>		<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		M5x0.8	<a href="#">0922 00 19</a>	11	9	11	0.010

## 0914 Equal Stud Elbow, Male BSPT Thread




	Nickel-plated brass 	<b>C</b>		<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	<a href="#">0914 00 10</a>	17	10	17	0.012
		R1/4	<a href="#">0914 00 13</a>	22.5	12	22.5	0.027
		R3/8	<a href="#">0914 00 17</a>	25.5	15	25.5	0.035
		R1/2	<a href="#">0914 00 21</a>	30	19	30	0.056
		R3/4	<a href="#">0914 00 27</a>	34.5	22	34.5	0.104
		R1	<a href="#">0914 00 34</a>	40.5	28	40.5	0.156

# Nickel-Plated Brass Adaptors




## 0910 Equal Y, Female BSPP Thread

	<p>Nickel-plated brass</p> 	<b>C</b>		<b>E</b>	<b>F</b>	<b>H</b>	<b>kg</b>
		G1/8	<a href="#">0910 00 10</a>	8	13	12	0.018
		G1/4	<a href="#">0910 00 13</a>	11	17	14	0.033
		G3/8	<a href="#">0910 00 17</a>	11.5	20	16	0.045
		G1/2	<a href="#">0910 00 21</a>	14	25	19	0.083




## 0911 Equal Y, Male BSPT/Female BSPP Thread

	<p>Nickel-plated brass</p> 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>F</b>	<b>H</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0911 00 10</a>	8	13	12	0.022
		R1/4	G1/4	<a href="#">0911 00 13</a>	11	17	14	0.038
		R3/8	G3/8	<a href="#">0911 00 17</a>	11.5	20	16	0.050
		R1/2	G1/2	<a href="#">0911 00 21</a>	14	25	19	0.103




## 0915 Equal Tee, Female BSPP and Metric Thread

	<p>Nickel-plated brass</p> 	<b>C</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>L/2</b>	<b>kg</b>
		M5x0.8	<a href="#">0915 00 19</a>	4	8	11	9	11	0.010
		G1/8	<a href="#">0915 00 10</a>	8	13	18.5	10	18.5	0.021
		G1/4	<a href="#">0915 00 13</a>	11	17	22.5	12	22.5	0.042
		G3/8	<a href="#">0915 00 17</a>	11.5	21	25.5	15	25.5	0.062
		G1/2	<a href="#">0915 00 21</a>	14	26	30	19	30	0.099
		G3/4	<a href="#">0915 00 27</a>	16.5	32	35.5	22	35.5	0.143
		G1	<a href="#">0915 00 34</a>	18	38.5	40	28	40	0.244

## 0923 Equal Stud Branch Tee, Female/Male Metric Thread




	<p>Nickel-plated brass</p> 	<b>C</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>L/2</b>	<b>kg</b>
		M5x0.8	<a href="#">0923 00 19</a>	4	8	11	9	11	0.009

## 0916 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread




	<p>Nickel-plated brass</p> 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>L/2</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0916 00 10</a>	8	13	17	10	18.5	0.019
		R1/4	G1/4	<a href="#">0916 00 13</a>	11	17	23.5	13	22.5	0.038
		R3/8	G3/8	<a href="#">0916 00 17</a>	11.5	21	25.5	15	25.5	0.076
		R1/2	G1/2	<a href="#">0916 00 21</a>	14	26	30	19	30	0.091
		R3/4	G3/4	<a href="#">0916 00 27</a>	16.5	32	34.5	22	35.5	0.140
		R1	G1	<a href="#">0916 00 34</a>	18	38.5	40.5	28	40.5	0.237

# Nickel-Plated Brass Adaptors




## 0924 Equal Stud Run Tee, Female/Male Metric Thread

	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>H1</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		M5x0.8	M5x0.8	<a href="#">0924 00 19</a>	4	8	11	11	9	11	0.009




## 0917 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>H1</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0917 00 10</a>	8	13	17	18.5	10	18.5	0.025
		R1/4	G1/4	<a href="#">0917 00 13</a>	11	17	22.5	22.5	12	22.5	0.038
		R3/8	G3/8	<a href="#">0917 00 17</a>	11.5	21	25.5	25.5	15	25.5	0.058
		R1/2	G1/2	<a href="#">0917 00 21</a>	14	26	30	30	19	30	0.090
		R3/4	G3/4	<a href="#">0917 00 27</a>	16.5	32	34.5	35.5	22	35.5	0.177
		R1	G1	<a href="#">0917 00 34</a>	18	38.5	40.5	40.5	28	40.5	0.219




## 0927 Equal Tee, Male BSPT Thread

	Nickel-plated brass 	<b>C</b>		<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	<a href="#">0927 00 10</a>	17	10	34	0.018
		R1/4	<a href="#">0927 00 13</a>	22.5	12	45	0.032
		R3/8	<a href="#">0927 00 17</a>	25.5	15	51	0.056
		R1/2	<a href="#">0927 00 21</a>	30	19	60	0.094
		R3/4	<a href="#">0927 00 27</a>	34.5	22	69	0.133
		R1	<a href="#">0927 00 34</a>	40.5	28	81	0.217

## 0928 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread




	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>H</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0928 00 10</a>	8	34	10	18.5	0.016
		R1/4	G1/4	<a href="#">0928 00 13</a>	11	45	12	22.5	0.044
		R3/8	G3/8	<a href="#">0928 00 17</a>	11.5	51	15	25.5	0.053
		R1/2	G1/2	<a href="#">0928 00 21</a>	14	60	19	30	0.111
		R3/4	G3/4	<a href="#">0928 00 27</a>	16.5	69	22	35.5	0.236
		R1	G1	<a href="#">0928 00 34</a>	18	81	28	40.5	0.225

## 0932 Equal Stud Run Tee, Male BSPT/Female BSPP Thread




	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>H</b>	<b>H1</b>	<b>J</b>	<b>L</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0932 00 10</a>	8	17	18.5	10	17	0.016
		R1/4	G1/4	<a href="#">0932 00 13</a>	11	22.5	22.5	12	22.5	0.035
		R3/8	G3/8	<a href="#">0932 00 17</a>	11.5	25.5	25.5	15	25.5	0.055
		R1/2	G1/2	<a href="#">0932 00 21</a>	14	30	30	19	30	0.091
		R3/4	G3/4	<a href="#">0932 00 27</a>	16.5	34.5	35.5	22	34.5	0.080
		R1	G1	<a href="#">0932 00 34</a>	18	40.5	40.5	28	40.5	0.226

# Nickel-Plated Brass Adaptors




## 0908 Equal Cross, Female BSPP Thread

	Nickel-plated brass 	<b>C</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>kg</b>
		G1/8	<a href="#">0908 00 10</a>	8	13	21	10	0.038
		G1/4	<a href="#">0908 00 13</a>	11	17	25.5	13	0.073
		G3/8	<a href="#">0908 00 17</a>	11.5	21	28	17	0.107
		G1/2	<a href="#">0908 00 21</a>	14	26	33.5	21	0.189




## 0909 Equal Cross, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>kg</b>
		R1/8	G1/8	<a href="#">0909 00 10</a>	8	13	18.5	10	0.034
		R1/4	G1/4	<a href="#">0909 00 13</a>	11	17	23.5	13	0.068
		R3/8	G3/8	<a href="#">0909 00 17</a>	11.5	21	26	17	0.099
		R1/2	G1/2	<a href="#">0909 00 21</a>	14	26	31	21	0.168

## 0903 Reducer, Male/Female BSPP Thread




	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>F</b>	<b>kg</b>
		G1/4	G1/8	<a href="#">0903 10 13</a>	8	6	0.004
		G3/8	G1/4	<a href="#">0903 13 17</a>	9	8	0.006
		G1/2	G3/8	<a href="#">0903 17 21</a>	10	10	0.010
		G3/4	G1/2	<a href="#">0903 21 27</a>	14	12	0.022
		G1	G3/4	<a href="#">0903 27 34</a>	20	17	0.036

## 0904 Reducer, Male BSPT/Female BSPP Thread

New 	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>F</b>	<b>L</b>	<b>kg</b>
		R1/4	G1/8	<a href="#">0904 10 13</a>	14	16	0.010
		R3/8	G1/8	<a href="#">0904 10 17</a>	17	16.5	0.020
			G1/4	<a href="#">0904 13 17</a>	17	16.5	0.015
		R1/2	G1/8	<a href="#">0904 10 21</a> *	22	19.5	0.046
			G1/4	<a href="#">0904 13 21</a>	22	19.5	0.032
			G3/8	<a href="#">0904 17 21</a>	22	19.5	0.025
		R3/4	G3/8	<a href="#">0904 17 27</a>	27	23.5	0.057
			G1/2	<a href="#">0904 21 27</a>	27	23.5	0.044
		R1	G1/2	<a href="#">0904 21 34</a> *	34	27	0.130
			G3/4	<a href="#">0904 27 34</a> *	34	27	0.770

\* Additional part numbers

## 0905 Reducer, Male BSPP/Female BSPP and Metric Thread

	Nickel-plated brass 	<b>C1</b>	<b>C2</b>		<b>E</b>	<b>F</b>	<b>L</b>	<b>kg</b>
		G1/8	M5x0.8	<a href="#">0905 19 10</a>	6	14	4.5	0.008
		G1/4	G1/8	<a href="#">0905 10 13</a>	8	17	5	0.011
		G3/8	G1/8	<a href="#">0905 10 17</a>	9	19	5	0.019
			G1/4	<a href="#">0905 13 17</a>	9	19	5	0.013
		G1/2	G1/4	<a href="#">0905 13 21</a>	10	24	5.5	0.032
			G3/8	<a href="#">0905 17 21</a>	10	24	5.5	0.022
		G3/4	G3/8	<a href="#">0905 17 27</a>	12	30	5.5	0.053
			G1/2	<a href="#">0905 21 27</a>	12	30	5.5	0.041




# Nickel-Plated Brass Adaptors

## 0933 Increaser, Male BSPT/Female BSPP Thread

New



Nickel-plated brass




C1	C2		E	F	L	kg
R1/8	G1/8	<a href="#">0933 00 10</a>	8	14	18	0.011
	G1/4	<a href="#">0933 10 13</a>	11	17	21.5	0.018
	G3/8	<a href="#">0933 10 17</a>	11.5	22	22.5	0.029
R1/4	G1/4	<a href="#">0933 00 13</a>	11	17	24.5	0.022
	G3/8	<a href="#">0933 13 17</a>	11.5	22	25.5	0.034
	G1/2	<a href="#">0933 13 21</a>	14	24	29	0.045
R3/8	G3/8	<a href="#">0933 17 17</a>	11.5	22	26	0.037
	G1/2	<a href="#">0933 17 21</a>	14	24	29.5	0.030
R1/2	G1/2	<a href="#">0933 00 21</a>	14	26	32	0.050
	G3/4	<a href="#">0933 21 27</a>	16.5	32	35	0.080

## 0906 Increaser, Male BSPP and Metric/Female BSPP Thread



Nickel-plated brass




C1	C2		E1	E2	F	L	kg
M5x0.8	G1/8	<a href="#">0906 10 19</a>	4	8	14	10	0.009
	G1/8	<a href="#">0906 00 10</a>	6	8	14	10	0.011
G1/8	G1/4	<a href="#">0906 10 13</a>	6	11	17	14	0.016
	G3/8	<a href="#">0906 10 17</a>	6	11.5	22	14.5	0.029
G1/4	G1/4	<a href="#">0906 00 13</a>	8	11	17	14	0.020
	G3/8	<a href="#">0906 13 17</a>	8	11.5	22	14.5	0.032
	G1/2	<a href="#">0906 13 21</a>	8	15	27	18	0.037
G3/8	G3/8	<a href="#">0906 00 17</a>	9	11.5	22	14.5	0.034
	G1/2	<a href="#">0906 17 21</a>	9	14	27	18	0.038
G1/2	G1/2	<a href="#">0906 00 21</a>	10	14	27	18	0.054

## 0907 Equal Extended Adaptor, Male/Female BSPP Thread



Nickel-plated brass




C		E	F	L	kg
G1/8	<a href="#">0907 00 10</a>	6	14	16	0.015
	<a href="#">0907 00 10 01</a>	6	14	36	0.029
G1/4	<a href="#">0907 00 13</a>	8	17	26	0.032
	<a href="#">0907 00 13 01</a>	8	17	43	0.046

## 0920 Bulkhead Connector, Female BSPP and Metric Thread






Nickel-plated brass






C	C1		F	F1	K <sub>max</sub>	L	L1	ØT	kg
M5x0.8	M10x1	<a href="#">0920 00 19</a>	14	14	7	10.5	3.5	10.5	0.012
G1/8	M16x1.5	<a href="#">0920 00 10</a>	19	22	9	14	4	16.5	0.029
G1/4	M20x1.5	<a href="#">0920 00 13</a>	24	27	15	21	4	20.5	0.056
G3/8	M26x1.5	<a href="#">0920 00 17</a>	30	32	14	21	5	26.5	0.095
G1/2	M28x1.5	<a href="#">0920 00 21</a>	32	36	20	27	6	28.5	0.115

# Nickel-Plated Brass Adaptors




## 0900 Equal and Unequal Adaptor, Male BSPT Thread

	Nickel-plated brass		<b>C1</b>	<b>C2</b>		<b>F</b>	<b>L</b>	<b>kg</b>
			R1/8	R1/8	<a href="#">0900 00 10</a>	12	19.5	0.008
			R1/8	R1/4	<a href="#">0900 10 13</a>	14	23.5	0.015
				R3/8	<a href="#">0900 10 17</a>	17	24	0.020
			R1/4	R1/4	<a href="#">0900 00 13</a>	14	27	0.017
				R3/8	<a href="#">0900 13 17</a>	17	27.5	0.026
			R3/8	R1/2	<a href="#">0900 13 21</a>	22	30.5	0.044
				R3/8	<a href="#">0900 00 17</a>	17	28	0.026
			R1/2	R1/2	<a href="#">0900 00 21</a>	22	31	0.046
				R3/4	<a href="#">0900 21 27</a>	27	33.5	0.044
			R3/4	R3/4	<a href="#">0900 00 27</a>	27	40	0.079
				R1	<a href="#">0900 27 34</a>	34	43	0.144
			R1	R1	<a href="#">0900 00 34</a>	34	45.5	0.153




## 0901 Equal and Unequal Adaptor, Male BSPP and Metric Thread

	Nickel-plated brass		<b>C1</b>	<b>C2</b>		<b>E</b>	<b>E1</b>	<b>F</b>	<b>L</b>	<b>kg</b>
			M5x0.8	M5x0.8	<a href="#">0901 00 19</a>	4	4	8	11.5	0.002
			M5x0.8	G1/8	<a href="#">0901 19 10</a>	4	6	14	14.5	0.008
				G1/8	<a href="#">0901 00 10</a>	6	6	14	16.5	0.009
			G1/8	G1/4	<a href="#">0901 10 13</a>	6	8	17	19	0.016
				G1/4	<a href="#">0901 00 13</a>	8	8	17	21	0.019
			G1/4	G3/8	<a href="#">0901 13 17</a>	8	9	19	22	0.023
				G3/8	<a href="#">0901 00 17</a>	9	9	19	23	0.025
			G3/8	G1/2	<a href="#">0901 17 21</a>	9	10	24	24.5	0.038
				G1/2	<a href="#">0901 00 21</a>	10	10	24	25.5	0.041

## 0192 Equal and Unequal Straight Adaptor, Male BSPT/BSPP Thread

	Nickel-plated brass		<b>C1</b>	<b>C2</b>		<b>E</b>	<b>F</b>	<b>L</b>	<b>kg</b>
			R1/8	G1/4	<a href="#">0192 10 13</a>	9.5	17	23.5	0.019
			R1/4	G1/4	<a href="#">0192 13 13</a>	9.5	17	27.5	0.024
				G1/2	<a href="#">0192 13 21</a>	11	27	31.5	0.068
			R3/8	G1/4	<a href="#">0192 17 13</a>	9.5	17	28	0.025
				G1/2	<a href="#">0192 17 21</a>	11	27	31.5	0.061
			R1/2	G1/2	<a href="#">0192 21 21</a>	11	27	34	0.061

## 0902 Equal and Unequal Adaptor, Female BSPP and Metric Thread

	Nickel-plated brass		<b>C1</b>	<b>C2</b>		<b>F</b>	<b>L</b>	<b>kg</b>
			M5x0.8	M5x0.8	<a href="#">0902 00 19</a>	8	11	0.003
			M5x0.8	G1/8	<a href="#">0902 19 10</a>	14	13	0.009
				G1/8	<a href="#">0902 00 10</a>	14	15	0.010
			G1/8	G1/4	<a href="#">0902 10 13</a>	17	19.5	0.017
				G3/8	<a href="#">0902 10 17</a>	22	20	0.028
			G1/4	G1/4	<a href="#">0902 00 13</a>	17	22	0.019
				G3/8	<a href="#">0902 13 17</a>	22	23	0.031
			G1/4	G1/2	<a href="#">0902 13 21</a>	27	27	0.033
				G3/8	<a href="#">0902 00 17</a>	22	24	0.034
			G3/8	G1/2	<a href="#">0902 17 21</a>	27	27.5	0.037
				G1/2	<a href="#">0902 00 21</a>	27	30	0.050
			G1/2	G3/4	<a href="#">0902 21 27</a>	30	30	0.077
				G3/4	<a href="#">0902 00 27</a>	30	32	0.080

# Nickel-Plated Brass Adaptors

## 0191 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

ØD	ØD1	C	Nickel-plated brass	E	F	K	L	kg
4	6	G1/4	<a href="#">0191 04 13</a>	9.5	17	5	22.5	0.019
	9	G1/4	<a href="#">0191 07 13</a>	9.5	17	5	22.5	0.022
7	9	G1/2	<a href="#">0191 07 21</a>	11	27	7	29.5	0.065
	12.2	G1/4	<a href="#">0191 10 13</a>	9.5	17	5	22.5	0.020
10	12.2	G1/2	<a href="#">0191 10 21</a>	11	27	7	29.5	0.061
	15.2	G1/4	<a href="#">0191 13 13</a>	9.5	17	5	22.5	0.022
13	15.2	G1/2	<a href="#">0191 13 21</a>	11	27	7	29.5	0.058
	16	G1/2	<a href="#">0191 16 21</a>	11	27	7	36.5	0.067

## 0931 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

ØD	ØD1	C	Nickel-plated brass	E	F	K	L	kg
6	7	G1/8	<a href="#">0931 06 10</a>	6	12	4	20	0.009
	7	G1/4	<a href="#">0931 06 13</a>	8	14	5	20	0.013
7	8	G1/8	<a href="#">0931 07 10</a>	6	12	4	20	0.009
	8	G1/4	<a href="#">0931 07 13</a>	8	14	5	20	0.013
8	8	G3/8	<a href="#">0931 07 17</a>	9	19	5	20	0.022
	9	G1/8	<a href="#">0931 08 10</a>	6	12	4	20	0.009
8	9	G1/4	<a href="#">0931 08 13</a>	8	14	5	20	0.014
	9	G3/8	<a href="#">0931 08 17</a>	9	19	5	20	0.022
10	12	G1/4	<a href="#">0931 10 13</a>	8	14	5	20	0.016
	12	G3/8	<a href="#">0931 10 17</a>	9	19	5	20	0.024
15	12	G1/2	<a href="#">0931 10 21</a>	10	22	6	22	0.031
	17	G3/8	<a href="#">0931 15 17</a>	9	19	6	24	0.030
18	17	G1/2	<a href="#">0931 15 21</a>	10	22	6	24	0.037
	20	G1/2	<a href="#">0931 18 21</a>	10	22	6	24	0.039

## 0934 Hose Barb Adaptor, Male BSPT Thread


ØD	C	Nickel-plated brass	F	L	L1	kg
6	R1/8	<a href="#">0934 06 10</a>	12	31.5	19	0.009
	R1/4	<a href="#">0934 06 13</a>	14	35	19	0.014
7	R1/8	<a href="#">0934 07 10</a>	12	31.5	19	0.009
	R1/4	<a href="#">0934 07 13</a>	14	35	19	0.014
8	R1/8	<a href="#">0934 08 10</a>	12	31.5	19	0.010
	R1/4	<a href="#">0934 08 13</a>	14	35	19	0.015
9	R1/8	<a href="#">0934 09 10</a>	12	31.5	19	0.012
	R1/4	<a href="#">0934 09 13</a>	14	35	19	0.015
10	R3/8	<a href="#">0934 09 17</a>	17	35.5	19	0.021
	R1/2	<a href="#">0934 09 21</a>	22	38.5	19	0.032
10	R1/8	<a href="#">0934 10 10</a>	12	32.5	20	0.010
	R1/4	<a href="#">0934 10 13</a>	14	36	20	0.015
10	R3/8	<a href="#">0934 10 17</a>	17	36.5	20	0.022
	R1/2	<a href="#">0934 10 21</a>	22	39.5	20	0.033
12	R1/4	<a href="#">0934 12 13</a>	14	36	20	0.019
	R3/8	<a href="#">0934 12 17</a>	17	36.5	20	0.021
14	R1/2	<a href="#">0934 12 21</a>	22	39.5	20	0.033
	R3/8	<a href="#">0934 14 17</a>	17	38.5	22	0.023
16	R1/2	<a href="#">0934 14 21</a>	22	41.5	22	0.036
	R3/8	<a href="#">0934 16 17</a>	17	38.5	22	0.026
16	R1/2	<a href="#">0934 16 21</a>	22	41.5	22	0.038
	R3/4	<a href="#">0934 16 27</a>	27	45	22	0.062
17	R3/8	<a href="#">0934 17 17</a>	18	40.5	24	0.030
	R1/2	<a href="#">0934 17 21</a>	22	43.5	24	0.043
18	R3/8	<a href="#">0934 18 17</a>	19	40.5	24	0.031
	R1/2	<a href="#">0934 18 21</a>	22	43.5	24	0.043
20	R3/4	<a href="#">0934 18 27</a>	27	47	24	0.062
	R3/8	<a href="#">0934 20 17</a>	22	41	24	0.038
20	R1/2	<a href="#">0934 20 21</a>	22	43.5	24	0.046


# Nickel-Plated Brass Adaptors

**0935**

Hose Barb Adaptor, Female BSPP Thread

**New**



ØD	C		E	F	L	L1	kg
6	G1/8	<a href="#">0935 06 10</a>	8	12	28.5	19	0.011
7	G1/8	<a href="#">0935 07 10</a>	8	12	28.5	19	0.012
	G1/4	<a href="#">0935 07 13</a>					
8	G1/4	<a href="#">0935 08 13</a>	11	15	31.5	19	0.019
9	G1/4	<a href="#">0935 09 13</a>	11	15	31.5	19	0.020
	G3/8	<a href="#">0935 09 17</a>					
10	G3/8	<a href="#">0935 10 17</a>	11.5	19	33	20	0.025
	G3/8	<a href="#">0935 12 17</a>					
12	G1/2	<a href="#">0935 12 21</a>	14	24	36	20	0.040


# Nickel-Plated Brass Plugs

## 0936 Internal Hexagon Head Plug, Male BSPT Thread

New



Nickel-plated brass




C		F	H	H1	kg
R1/8	<a href="#">0936 00 10</a>	5	8	8	0.002
R1/4	<a href="#">0936 00 13</a>	6	10	7	0.007
R3/8	<a href="#">0936 00 17</a>	8	11	7.5	0.013
R1/2	<a href="#">0936 00 21</a>	10	13	8	0.025

## 0919 Internal Hexagon Head Plug, Male BSPP and Metric Thread



Nickel-plated brass



C		E	F	G	H	kg
M5x0.8	<a href="#">0919 00 19</a>	4	2.5	8	7.5	0.001
G1/8	<a href="#">0919 00 10</a>	6	3	15	10	0.007
G1/4	<a href="#">0919 00 13</a>	8	6	18	12	0.013
G3/8	<a href="#">0919 00 17</a>	9	8	21	13	0.021
G1/2	<a href="#">0919 00 21</a>	10	10	25	14.5	0.036
G3/4	<a href="#">0919 00 27</a>	11	30	-	17	0.050
G1	<a href="#">0919 00 34</a>	13	38	-	19	0.076

## Related Products

You will find all related products associated with this range of accessories in our general Catalogue and on our Internet website, [www.parkerlegris.com](http://www.parkerlegris.com).

### LF 3600 Push-in Fittings



In order to meet your **technical and environment requirements**, Parker Legris designed this range of metal fittings (brass nickel-plated), offering **robustness, reliability** and **resistance to industrial fluids** for the most demanding environments.

### Function Fittings



Parker Legris flow control regulators with polymer, nickel-plated brass or aluminium bodies, external or recessed adjustment screws offer **precise adjustment, accuracy** and **compactness** providing the solution for all applications.

## Tubing

### Polyamide Tubing (PA)



**Tried-and-tested** for industrial or vehicle applications, PA tubing guarantees **excellent durability** due to its stable long-term mechanical properties. Parker Legris' special grade of semi-rigid polyamide is manufactured according to our **Eco-Design** approach for higher performance.

### Polyurethane Tubing (PU)



Polyurethane's **3 specific materials** - ether, ester and food-grade "crystal" - offer excellent flexibility and outstanding use in a wide range of applications, allowing for up to **50% space reduction** when compared to semi-rigid PA tubing.

### Fireproof PA Tubing



This **single-layer fireproof** tubing not only combines excellent resistance to pressure, temperature and flame, but also guarantees **non-toxic smoke** resulting from burn-off. This tubing eliminates the need for a stripping tool, thus preventing the risk of tube damage prior to connection.

### Polyethylene Tubing (PE)



Parker Legris offers two types of polyethylene tubing: **"Advanced PE" 50% reticulated** and **Low Density PE**. Our range of "Advanced PE" tubing is designed for demanding environments, especially that of water treatment, without compromising operator **safety**.



## Together, we can connect you to the best in technology. Better than ever before.

In this updated edition of the Parker Legris catalogue, we have developed the content, structure and layout to enable you to find the products and information you require as quickly as possible. 31 complementary ranges and more than 1000 additional part numbers have been included, widening the choice of solutions available in order to meet your requirements more effectively. By putting our knowledge and expertise at your fingertips, we strive to provide the day-to-day support you need when designing your industrial equipment.



aerospace  
climate control  
electromechanical  
filtration  
fluid & gas handling  
hydraulics  
pneumatics  
process control  
sealing & shielding



ENGINEERING YOUR SUCCESS.

[www.parkerlegris.com](http://www.parkerlegris.com)

# Parker Worldwide

## Europe, Middle East, Africa

**AE – United Arab Emirates,** Dubai  
Tel: +971 4 8127100  
parker.me@parker.com

**AT – Austria,** Wiener Neustadt  
Tel: +43 (0)2622 23501-0  
parker.austria@parker.com

**AT – Eastern Europe,** Wiener Neustadt  
Tel: +43 (0)2622 23501 900  
parker.easteurope@parker.com

**AZ – Azerbaijan,** Baku  
Tel: +994 50 2233 458  
parker.azerbaijan@parker.com

**BE/LU – Belgium,** Nivelles  
Tel: +32 (0)67 280 900  
parker.belgium@parker.com

**BG – Bulgaria,** Sofia  
Tel: +359 2 980 1344  
parker.bulgaria@parker.com

**BY – Belarus,** Minsk  
Tel: +375 17 209 9399  
parker.belarus@parker.com

**CH – Switzerland,** Etoy  
Tel: +41 (0)21 821 87 00  
parker.switzerland@parker.com

**CZ – Czech Republic,** Klecany  
Tel: +420 284 083 111  
parker.czechrepublic@parker.com

**DE – Germany,** Kaarst  
Tel: +49 (0)2131 4016 0  
parker.germany@parker.com

**DK – Denmark,** Ballerup  
Tel: +45 43 56 04 00  
parker.denmark@parker.com

**ES – Spain,** Madrid  
Tel: +34 902 330 001  
parker.spain@parker.com

**FI – Finland,** Vantaa  
Tel: +358 (0)20 753 2500  
parker.finland@parker.com

**FR – France,** Contamine s/Arve  
Tel: +33 (0)4 50 25 80 25  
parker.france@parker.com

**GR – Greece,** Athens  
Tel: +30 210 933 6450  
parker.greece@parker.com

**HU – Hungary,** Budaörs  
Tel: +36 23 885 470  
parker.hungary@parker.com

**IE – Ireland,** Dublin  
Tel: +353 (0)1 466 6370  
parker.ireland@parker.com

**IT – Italy,** Corsico (MI)  
Tel: +39 02 45 19 21  
parker.italy@parker.com

**KZ – Kazakhstan,** Almaty  
Tel: +7 7273 561 000  
parker.easteurope@parker.com

**NL – The Netherlands,** Oldenzaal  
Tel: +31 (0)541 585 000  
parker.nl@parker.com

**NO – Norway,** Asker  
Tel: +47 66 75 34 00  
parker.norway@parker.com

**PL – Poland,** Warsaw  
Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**PT – Portugal,** Leca da Palmeira  
Tel: +351 22 999 7360  
parker.portugal@parker.com

**RO – Romania,** Bucharest  
Tel: +40 21 252 1382  
parker.romania@parker.com

**RU – Russia,** Moscow  
Tel: +7 495 645-2156  
parker.russia@parker.com

**SE – Sweden,** Spånga  
Tel: +46 (0)8 59 79 50 00  
parker.sweden@parker.com

**SK – Slovakia,** Banská Bystrica  
Tel: +421 484 162 252  
parker.slovakia@parker.com

**SL – Slovenia,** Novo Mesto  
Tel: +386 7 337 6650  
parker.slovenia@parker.com

**TR – Turkey,** Istanbul  
Tel: +90 216 4997081  
parker.turkey@parker.com

**UA – Ukraine,** Kiev  
Tel: +380 44 494 2731  
parker.ukraine@parker.com

**UK – United Kingdom,** Warwick  
Tel: +44 (0)1926 317 878  
parker.uk@parker.com

**ZA – South Africa,** Kempton Park  
Tel: +27 (0)11 961 0700  
parker.southafrica@parker.com

## North America

**CA – Canada,** Milton, Ontario  
Tel: +1 905 693 3000

**US – USA,** Cleveland  
Tel: +1 216 896 3000

## Asia Pacific

**AU – Australia,** Castle Hill  
Tel: +61 (0)2-9634 7777

**CN – China,** Shanghai  
Tel: +86 21 2899 5000

**HK – Hong Kong**  
Tel: +852 2428 8008

**IN – India,** Gurgaon  
Tel: +91 124 459 0600  
legris.india@parker.com

**JP – Japan,** Tokyo  
Tel: +81 (0)3 6408 3901

**KR – South Korea,** Seoul  
Tel: +82 2 559 0400

**MY – Malaysia,** Shah Alam  
Tel: +60 3 7849 0800

**NZ – New Zealand,** Mt Wellington  
Tel: +64 9 574 1744

**SG – Singapore**  
Tel: +65 6887 6300

**TH – Thailand,** Bangkok  
Tel: +662 186 7000-99

**TW – Taiwan,** Taipei  
Tel: +886 2 2298 8987

## South America

**AR – Argentina,** Buenos Aires  
Tel: +54 3327 44 4129

**BR – Brazil,** Sao Jose dos Campos  
Tel: +55 800 727 5374

**CL – Chile,** Santiago  
Tel: +56 2 623 1216

**MX – Mexico,** Apodaca  
Tel: +52 81 8156 6000

Ed. 2013-04

BUL/0541/UK

© 2013 Parker Hannifin Corporation. All rights reserved.

Your Parker Distributor



Fluid System Connectors Europe  
**Parker Hannifin Manufacturing France SAS**  
Parker Hannifin Corporation  
CS 46911 - 74 rue de Paris  
35069 Rennes  
Phone: +33 (0)2 99 25 55 00  
Fax: +33 (0)2 99 25 55 99  
www.parkerlegris.com

**ARA**<sup>®</sup>  
PNEUMATIK  
53-012 Wrocław tel. 71 364 72 82  
ul. Wysięgowa 38 fax 71 364 72 83  
www.arapneumatik.pl

